


CONSTRUCTION	Tufting 5/64" cut pile	STAIR SUITABILITY	EN 1963
STRUCTURE	Tufté 5/64" velours	ESCALIERS	B: occasional use
STRUKTUR	Getuftet 5/64" Velours	TREPPENEIGNUNG	
STRUCTUUR	Getuft 5/64" velours	TRAPPENGESCHIKTHEID	
PILE MATERIAL	100% PA 6 IMPREL®	PERMANENTLY ANTISTATIC	ISO 6356
COMPOSITION DU VELOURS		ANTISTATIQUE PERMANENT	< 2 kV
POLMATERIAL		PERMANENT ANTISTATISCH	
POOLMATERIAAL		PERMANENT ANTISTATISCH	
PRIMARY BACKING	Woven PP	IMPACT NOISE RATING	ISO 140-8
SUPPORT	PP tissé	ISOLATION PHONIQUE	28 dB ΔLw
TRÄGERMATERIAL	PP Bändchengewebe	TRITTSCHALLVERBESSERUNG	
TUFTDOEK	Woven PP	GELUIDSISOLATIE	
SECONDARY BACKING	Ultratex	SOUND ABSORPTION	ISO 354
DOSSIER		ABSORPTION PHONIQUE	0,30 αw
RÜCKEN		SCHALLABSORPTIONSGRAD	
TAPIJTRUG		GELUIDSABSORPTIE	
PILE WEIGHT	Ca. 620 gr/m ²	THERMAL RESISTANCE	ISO 8302
POIDS DU VELOURS		RÉSISTANCE THERMIQUE	0,13 m ² K/W
POLEINSATZGEWICHT		WÄRMEDURCHLASSWIDERSTAND	
POOLGEWICHT		WARMTEDOORLAATWEERSTAND	
TOTAL WEIGHT	Ca. 1.570 gr/m ²	FASTNESS TO LIGHT	ISO 105-B02
POIDS TOTAL		SOLIDITÉ A LA LUMIÈRE	≥ 5-6
GESAMTGEWICHT		LICHTECHTHEIT	
TOTAAL GEWICHT		LICHTECHTHEID	
PILE HEIGHT	Ca. 4,5 mm	COLOUR FASTNESS TO WATER	EN ISO 105-E01
EPAISSEUR DU VELOURS		SOLIDITÉ À L'EAU	≥ 4-5
POLHÖHE		WASSERECHTHEIT	
POOLHOOGTE		WATERECHTHEID	
TOTAL HEIGHT	Ca. 8 mm	FIRE RESISTANCE	EN 13501-1
EPAISSEUR TOTAL		COMPORTEMENT AU FEU	Cfl-s1 (if glued)
GESAMTHÖHE		BRENNVERHALTEN	
TOTALE DIKTE		BRANDGEDRAG	
TUFT DENSITY	Ca. 400.000/m ²	RUBBING FASTNESS	EN ISO 105-X12
NOMBRES DE POINTS		SOLIDITÉ AU FROTTEMENT	≥ 4
NOPPENZAHL		REIBECHTHEIT	
AANTAL PUNTEN		WRIJFECHTHEID	
PILE DENSITY	Ca. 0,100 g/cm ³	NUMBER OF COLOURS	16
DENSITÉ DU VELOURS		NOMBRES DE COULEURS	
POLROHDICHTE		ANZAHL FARBEN	
POOLDICHTHEID		AANTAL KLEUREN	
CLASSIFICATION	EN 1307	WIDTH	EN ISO 3018
CLASSEMENT	32 - LC2	LARGEUR	ca. 400 cm (16 colours)
KLASSIFIKATION		BREITE	ca. 500 cm (5 colours)
CLASSIFICATIE		BREEDTE	
UPEC	U3 P3 E1 C0 Certification CSTB: 04/203		
CASTOR CHAIR SUITABILITY	EN 985		
CHAISE À ROULETTES	A: intensive use		
STUHLROLLENEIGNUNG			
ROLSTOELGESCHIKTHEID			



EN14041




13

Balta Industries - Kanegem-
straat 15 - BE 8700 Tielt


DOP: 1011#IF0ACV

Textile Floor Covering EN1307
Notified body 0493



www.baltamediabank.com

EAC




REG. NR
DBC040FB

www.pro-dis.info



QB UPEC

moquettes touffetées et tissées en lés
<http://evaluation.cstb.fr>



▲ 33 4 m



▲ 30 4 & 5 m



▲ 38 4 m



▲ 34 4 m



▲ 40 4 & 5 m



▲ 153 4 m




▲ 97 4 & 5 m




▲ 98 4 & 5 m



▲ 198 4 m



▲ 47 4 m



▲ 256 4 m




▲ 179 4 m




▲ 279 4 m



▲ 227 4 m



▲ 16 4 & 5 m



▲ 12 4 m