


|                                                                                              |                                                                                                                                      |                                                                                                      |                                                                     |
|----------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------|
| CONSTRUCTION<br>STRUCTURE<br>STRUKTUR<br>STRUCTUUR                                           | ituft 1/12" loop tipsheared<br>ituft 1/12" bouclé tipsheared<br>ituft 1/12" tipsheared-Schlinge<br>ituft 1/12" lussenpool tipsheared | STAIR SUITABILITY<br>ESCALIERS<br>TREPPENEIGNUNG<br>TRAPPENGESCHIKTHEID                              | EN 1963<br>A: intensive use                                         |
| PILE MATERIAL<br>COMPOSITION DU VELOURS<br>POLMATERIAL<br>POOLMATERIAAL                      | 100% PA 6 IMPREL®<br>Solution Dyed                                                                                                   | PERMANENTLY ANTISTATIC<br>ANTISTATIQUE PERMANENT<br>PERMANENT ANTISTATISCH<br>PERMANENT ANTISTATISCH | ISO 6356<br>≤ 2 kV                                                  |
| PRIMARY BACKING<br>SUPPORT<br>TRÄGERMATERIAL<br>TUFTDOEK                                     | Non woven PES<br>PES non tissé<br>PES Vlies<br>PES Vilt                                                                              | IMPACT NOISE RATING<br>ISOLATION PHONIQUE<br>TRITTSCHALLVERBESSERUNG<br>GELUIDSISOLATIE              | ISO 140-8<br>26 dB ΔLw                                              |
| SECONDARY BACKING<br>DOSSIER<br>RÜCKEN<br>TAPIJTRUG                                          | Twinback                                                                                                                             | SOUND ABSORPTION<br>ABSORPTION PHONIQUE<br>SCHALLABSORPTIONSGRAD                                     | ISO 354<br>0,25 αw                                                  |
| PILE WEIGHT<br>POIDS DU VELOURS<br>POLEINSATZGEWICHT<br>POOLGEWICHT                          | Ca. 800 gr/m²                                                                                                                        | THERMAL RESISTANCE<br>RÉSISTANCE THERMIQUE<br>WÄRMEDURCHLASSWIDERSTAND<br>WARMTEDOORLAATWEERSTAND    | ISO 8302<br>0,11 m² K/W                                             |
| TOTAL WEIGHT<br>POIDS TOTAL<br>GESAMTGEWICHT<br>TOTAAL GEWICHT                               | Ca. 2.400 gr/m²                                                                                                                      | FASTNESS TO LIGHT<br>SOLIDITÉ À LA LUMIÈRE<br>LICHTECHTHEIT<br>LICHTECHTHEID                         | ISO 105-B02<br>≥ 7                                                  |
| PILE HEIGHT<br>EPAISSEUR DU VELOURS<br>POLHÖHE<br>POOLHOOGTE                                 | Ca. 3,6-5,2 mm                                                                                                                       | COLOUR FASTNESS TO WATER<br>SOLIDITÉ À L'EAU<br>WASSERECHTHEIT<br>WATERECHTHEID                      | EN ISO 105-E01<br>≥ 4-5                                             |
| TOTAL HEIGHT<br>EPAISSEUR TOTAL<br>GESAMTHÖHE<br>TOTALE DIKTE                                | Ca. 7,7-9,3 mm                                                                                                                       | FIRE RESISTANCE<br>COMPORTEMENT AU FEU<br>BRENNVERHALTEN<br>BRANDGEDRAG                              | EN 13501-1<br>Cfl-s1                                                |
| TUFT DENSITY<br>NOMBRES DE POINTS<br>NOPPENZAHL<br>AANTAL PUNTEN                             | Ca. 282.000/m²                                                                                                                       | RUBBING FASTNESS<br>SOLIDITÉ AU FROTTEMENT<br>REIBECHTHEIT<br>WRIJFECHTHEID                          | EN ISO 105-X12<br>≥ 4                                               |
| PILE DENSITY<br>DENSITÉ DU VELOURS<br>POLROHDICHTE<br>POOLDICHTHEID                          | Ca. 0,122 g/cm³                                                                                                                      | NUMBER OF COLOURS<br>NOMBRES DE COULEURS<br>ANZAHL FARBEN<br>AANTAL KLEUREN                          | 9                                                                   |
| CLASSIFICATION<br>CLASSEMENT<br>KLASSIFIKATION<br>CLASSIFICATIE                              | EN 1307<br>32 - LC2                                                                                                                  | WIDTH<br>LARGEUR<br>BREITE<br>BREEDTE                                                                | EN ISO 3018<br>ca. 400 cm                                           |
| CASTOR CHAIR SUITABILITY<br>CHAISE À ROULETTES<br>STUHLROLLENEIGNUNG<br>ROLSTOELGESCHIKTHEID | EN 985<br>A: intensive use                                                                                                           | DESIGN REPEAT CM<br>RACCORD CM<br>RAPPORT CM<br>DESSINRAPPORT CM                                     | ca. 199 (W) x<br>ca. 424 (H)<br>repeatless installation<br>possible |







▲ 35



▲ 47




▲ 96



▲ 95




▲ 90



▲ 27



▲ 77



▲ 97



▲ 98