

# promenade<sub>AB</sub> / pm+dessin<sub>AB</sub>

CONSTRUCTION	Tufting 1/10" saxony
STRUCTURE	Tufté 1/10" saxony
STRUKTUR	Getuftet 1/10" saxony
STRUCTUUR	Getuft 1/10" saxony
PILE MATERIAL	100% PA 6 IMPREL®
COMPOSITION DU VELOURS	
POLMATERIAL	
POOLMATERIAAL	
PRIMARY BACKING	Non woven PES
SUPPORT	Non tissé
TRÄGERMATERIAL	Vlies
TUFTDOEK	Felt
SECONDARY BACKING	Action Back
DOSSIER	
RÜCKEN	
TAPIJTRUG	
PILE WEIGHT	Ca. 900 gr/m <sup>2</sup>
POIDS DU VELOURS	
POLEINSATZGEWICHT	
POOLGEWICHT	
TOTAL WEIGHT	Ca. 1.875 gr/m <sup>2</sup>
POIDS TOTAL	
GESAMTGEWICHT	
TOTAAL GEWICHT	
PILE HEIGHT	Ca. 4 mm
EPAISSEUR DU VELOURS	
POLHÖHE	
POOLHOOGTE	
TOTAL HEIGHT	Ca. 7 mm
EPAISSEUR TOTALE	
GESAMTHÖHE	
TOTALE DIKTE	
TUFT DENSITY	Ca. 170 000/m <sup>2</sup>
NOMBRES DE POINTS	
NOPPENZAHL	
AANTAL PUNTEN	
PILE DENSITY	Ca. 0.143 g/cm <sup>3</sup>
DENSITÉ DU VELOURS	
POLROHDICHTÉ	
POOLDICHTHEID	
CLASSIFICATION	EN 1307
CLASSEMENT	32 - LC2
KLASSIFIKATION	
CLASSIFICATIE	
UPEC	U3 P3 E1 C0 Certification CSTB: 10/276
CASTOR CHAIR SUITABILITY	EN 985
CHAISE À ROULETTES	A: intensive use
STUHLROLLENEIGNUNG	
ROLSTOELGESCHIKTHEID	
STAIR SUITABILITY	EN 1963
ESCALIERS	A: intensive use
TREPPENEIGNUNG	
TRAPPENGESCHIKTHEID	

PERMANENTLY ANTISTATIC ISO 6356  
ANTISTATIQUE PERMANENT ≤ 2 kV  
PERMANENT ANTISTATISCH  
PERMANENT ANTISTATISCH

IMPACT NOISE RATING ISO 140-8  
ISOLATION PHONIQUE 24 dB ΔLw  
TRITTSCHALLVERBESSERUNG  
GELUIDSISOLATIE

SOUND ABSORPTION ISO 354  
ABSORPTION PHONIQUE 0.20 αw  
SCHALLABSORPTIONSGRAD  
GELUIDSABSORPTIE

THERMAL RESISTANCE ISO 8302  
RÉSISTANCE THERMIQUE 0.08 m<sup>2</sup> K/W  
WÄRMEDURCHLASSWIDERSTAND  
WARMTEDOORLAATWEERSTAND

FASTNESS TO LIGHT ISO 105-B02  
SOLIDITÉ A LA LUMIÈRE ≥ 5-6  
LICHTECHTHEIT  
LICHTECHTHEID

COLOUR FASTNESS TO WATER EN ISO 105-E01  
SOLIDITÉ À L'EAU ≥ 4-5  
WASSERECHEITHEIT  
WATERECHEITHEID

FIRE RESISTANCE EN 13501-1  
COMPORTEMENT AU FEU Bfl-s1 (if glued)  
BRENNVERHALTEN  
BRANDGEDRAG

RUBBING FASTNESS EN ISO 105-X12  
SOLIDITÉ AU FROTTEMENT ≥ 4  
REIBECHTHEIT  
WRIJFECHTHEID


WIDTH EN ISO 3018  
LARGEUR ca. 400 cm  
BREITE  
BREEDE



Suitable for Allergic Persons  
Wall to wall carpet of allergen-tested material  
3.2-2384/06












EN14041



16

Balta Industries - Kanegem-  
straat 15 - BE 8700 Tielt

**DOP: 1011#IE0ABV**

Textile Floor Covering EN1307  
Notified body 2401



[www.baltamediabank.com](http://www.baltamediabank.com)



moquettes touffées et tissées en lés  
<http://evaluation.cstb.fr>

UPEC

REG. NR  
**1721C645**  
[www.pro-dis.info](http://www.pro-dis.info)

